



CONTROLLER PIN OUT

TAB	FUNCTION
1	THROTTLE
2	THROTTLE REVERSE
3	1/2 SPEED
4	KSI VOLTAGE
B+	BATTERY POSITIVE
B-	BATTERY NEGATIVE
M-	MOTOR MINUS

NOTES:

- * FUSES REQUIRED FOR ALL INSTALLATIONS
- * DIODE REQUIRED ACROSS COILS / RELAYS
- * PRE-CHARGE RESISTOR REQUIRED
- > ASSUMES FOOTSWITCH IS OPEN WHEN THROTTLE OFF
- > ALLTRAX RESERVES THE RIGHT TO CHANGE DOCUMENTATION WITHOUT NOTICE
- > ALLTRAX MAKES NO WARRANTY AS TO THE ACCURACY, SUFFICIENCY, OR SUITABILITY OF ANY TECHNICAL OR OTHER INFORMATION PROVIDED
- > SEE OPERATORS MANUAL FOR MORE INFORMATION

* HIGH CURRENT WIRING IN BOLD *

NPX48XXEZ
to EZ-GO
Year: 1994-Present
Stock vehicles only

REV.	ECO.	DATE	APVD	REVISIONS
A	041708	41708	RC	

DWG SCALE	NIS
DRAMIN T.Thorne	111306
ENGR D.Crockett	111306

FILE:	SIZE	DOCUMENT NO.	REV.
DWG-NPX-EZGO-Wire-Diagram	A	Doc100-077	A

ALLTRAX
1111 Cheney Creek Rd.
Grants Pass, OR 97527
PHONE:(541) 476-3565

TITLE
NPX-EZGO - 1206 Replacement
Wiring Diagram