

EZ-G-O
APPLICATION & CROSS REFERENCE GUIDE

| Model / Year | Throttle | Identifiers | Stock* Controller | Mild* Performance | Wild* Performance | Extreme* Performance |
|---|-----------------|---|------------------------------|------------------------------|------------------------------|---------------------------------|
| 94 & Older Marathon Car | 0-5K | Four, ¼ inch tabs | SR48300 | SR48400 | SR48500 | SR48600 |
| 95 & Newer Medalist & TXT | ITS | Throttle located under floorboard 5 pin connector | SR48300 | SR48400 | SR48500 | SR48600 |
| 1997-2001 DCS | ITS | 9 pin Connector F/R by driver's leg | XCT48300-DCS | XCT48400- DCS | XCT48500- DCS | |
| 2001- Present PDS | ITS | 4 Multi-pin connectors F/R Switch on Dash | XCT48300- PDS | XCT48400- PDS | XCT48500- PDS | |
| 2010 to Present TXT 48 | ITS | 48v battery pack 16 pin connector on black controller | XCT48300-TXT48 | XCT48400- TXT48 | XCT48500- TXT48 | |

Performance upgrades – use correctly sized solenoids and wires.

See Technical Note #10 for more information

**Stock – No Upgrades; Mild – Big tires OR motor, but not both; Wild – Big Tires AND Motor or NEV's; Extreme – Hunting buggy, EV's and other high performance applications.*